

NAME

pce-rc759 – RC759 Piccoline emulator

SYNOPSIS

pce-rc759 [*options*]

DESCRIPTION

pce-759(1) is an RC759 Piccoline emulator.

OPTIONS

-c, --config *file*

Set the config file name.

-d, --path *string*

Add a directory to the search path.

The search path is used if an input file (such as a ROM image or a disk image) is specified with a relative file name. In that case the file is searched for in all directories of the search path. The current directory is always implicitly added to the end of the search path.

The directory name can be prefixed by one of these characters:

- +** Add the directory to the end of the search path
- Add the directory to the beginning of the search path
- =** Clear the search path before adding the directory

The default is to add the directory to the end of the search path.

-g, --video *string*

Set the video type to either **color** or **mono**.

-l, --log *file*

Write log messages to the file specified instead of stdout.

-q, --quiet

Don't print anything to stdout or stderr.

-r, --run

Start running immediately.

-R, --no-monitor

Start running immediately and never fall back to the monitor. This is useful if stdout is not visible, for example because the emulator was started directly from a graphical user interface such as X or Windows.

-s, --speed *factor*

Set the initial speed factor. This overrides a value specified in the configuration file.

-t, --terminal *string*

Set the terminal device. Possible devices are **null**, **x11** and **sdl**.

-v, --verbose

Verbose operation. This is highly recommended.

--help Print usage information

--version

Print version information

SEE ALSO

cpmtools(1)

AUTHOR

Hampa Hug <hampa@hampa.ch>